

UXHM 耐圧防爆構造フレキシブルフィッティング

防爆構造: d2G4

UXHM-F



UXHM-M



[標準] 材質: スチール / 表面処理: クロメートメッキ

[非標準] 材質: プラス / 表面処理: ニッケルメッキ

型式: 寸法一覧表

型式	接合ネジ			外形寸法(mm)					有効長 L (mm)	質量 (kg)
	サイズ	T1	T2	A1	A2	φd	H	φD		
UXHM10F	16	PF1/2	PF1/2	15	15	14	35	37	500	0.50
UXHM10M									700	0.63
									1000	0.76
UXHM20F	22	PF3/4	PF3/4	15	15	19	41	43	500	0.70
UXHM20M									700	0.85
									1000	1.00
UXHM30F	28	PF1	PF1	19	19	24	50	53	500	0.98
UXHM30M									700	1.30
									1000	1.60
UXHM40F	36	PF1 1/4	PF1 1/4	19	19	30	58	61	500	1.45
UXHM40M									700	1.95
									1000	2.30
UXHM50F	42	PF1 1/2	PF1 1/2	19	19	36	67	70	500	1.95
UXHM50M									700	2.40
									1000	2.70
UXHM60F	54	PF2	PF2	21	21	48	82	85	500	2.60
UXHM60M									700	3.20
									1000	3.80
UXHM70F	70	PF2 1/2	PF2 1/2	23	23	60	97	100	500	4.30
UXHM70M									700	5.50
									1000	6.60
UXHM80F	82	PF3	PF3	25	25	72	114	118	500	4.90
UXHM80M									700	5.90
									1000	7.00